DESCO 622

Hydrocarbon Service Low Temperature

GRM FLOW PRODUCTS

PERFORMANCE UNDER PRESSURE SINCE 1986

Description:

Desco 622 greatly expands the effective temperature range of synthetic valve lubricants while providing improved fuel and oil resistance. Formulated with 100% synthetic base oil reinforced with state-of-the-art additive package to provide superior sealing and lubricating properties.

Service Recommendations:

Aliphatic hydrocarbons including, butane, crude distillates, fuels, oils and propane. Also, dilute acids, dilute unleaded gasoline.

Typical Characteristics:

NLGI	2
ASTM Penetration	
Bulk	250 - 280
Large stick	80 - 100
Small stick	40 - 80
Base oil type	synthetic
Color	amber
Temperature range	-50°F to +400°F (-46°C to +204°C)

Packaging Information:

Item No.	Unit Size	Quantity	Ship Wt.
LL622110	"B" stick 3/8" x 1 1/2"	72 /box	.5 lbs.
LL622130	"D" stick 1/2" x 2 1/4"	28 /box	.5 lbs.
LL622150	"J" stick 1 3/8" x 8 1/2"	16 /box	9 lbs.
LL622160	"K" stick 1 1/2" x 10 1/2"	12 /box	10 lbs.
LL622200	14 oz. cartridges	10 ctn.	12 lbs.
LL622010	10 lb can	1 each	11 lbs.
LL622020	20 lb can	1 each	23 lbs.
LL622040	40 lb pail	1 each	45 lbs.
LL622120	120 lb keg c/w liner	1 each	130 lbs.
LL622400	400 lb drum c/w liner	1 each	438 lbs.

Supplying the Highest Quality Products to the Valve Industry

#310, 8810 - 15 St
Edmonton, AB | T6P 0B9 | 780.416.4823
GRMFLOW.COM SALES@GRMFLOW.COM