DESCO DRY MOLY
Lube

GRM FLOW PRODUCTS

PERFORMANCE UNDER PRESSURE SINCE 1986

Description:

Desco Dry Moly Lube is an extreme temperature pressure lubricant. It is inert to water, oil, alkalies and most acids. Desco Dry Moly Lube leaves a dry lubricated surface. It is especially suitable in areas where oil and grease cannot be used. Typical uses are automotive, refineries, chemical plants, paper mills, foundries, machine shops and other manufacturing facilities. Dry Moly Lube is a heavy concentrate of micro-sized colloidal molybdenum disulfide lubricating solids in a fast evaporating carrier that has exceptional penetrating and spreading ability. It is a tough nonconductive, dry film lubricant with strong surface bond after the carrier evaporates. It does not attract or retain grit. It is resistant to extreme temperatures and to chemical degradation. It dries to the touch in 60 seconds.

- Shake can vigorously before use.
- Clean and dry surface to be coated.
- Hold can 8 to 10 inches from surface.
- Apply thin uniform coating.
- Invert can and clear nozzle with a jet of clear gas after each use.
- Desco Dry Moly can be removed with chlorinated solvent.

Typical Characteristics:

Color	black

Packaging Information:

Item No.	Unit Size	Quantity	Ship Wt.
LM932500	14 oz. aero	12 /ctn	14 lbs.

Supplying the Highest Quality Products to the Valve Industry

#310, 8810 - 15 St
Edmonton, AB | T6P 0B9 | 780.416.4823
GRMFLOW.COM SALES@GRMFLOW.COM