

**LUBRICANTS****Desco 620***FOR WKM Type Valves*DESCRIPTION

Desco 620 is a “peanut butter” type of synthetic lubricant/sealant used in gate valves with liquid and gas hydrocarbon service. It has a 100% synthetic fluid base and is also available in a softer version referred to as “creamy”.

SERVICE RECOMMENDATIONS

Aliphatic hydrocarbons, alkalis, dilute acids, salt water and water.

TYPICAL CHARACTERISTICS

Appearance	Brown, “peanut butter”
NLGI	0/00
Penetration (ASTM D217)	355-385 / 410-415
Worked Penetration, 60x (ASTM D217)	355-385 / 410-415
Base Oil	Natural and synthetic
Base Oil Viscosity	500 cSt at 40° C
Base Oil Pour Point	-4°F (-20°C)
Thickener	Inorganic
Additives	Antioxidant package
Solids Content	Natural minerals
Specic Gravity	1.5
Density (lb/gal)	12.6
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	450°F (232°C)
Temperature Range	0°F to 300°F (-18°C to 149°C)

PACKAGING INFORMATION

<b>PART #</b>	<b>UNIT SIZE</b>	<b>CONTAINER</b>
LL620010	10 lb	Can
LL620020	20 lb	Can
LL620040	50 lb	Pail
LL620120	150 lb	Drum
LL620400	400 lb	Drum

