

INJECTABLE PACKING**Desco 625 Pak**

*Injectable Packaging with PTFE
and Aramid Fibers*

DESCRIPTION

Desco 625 Pak injectable packing contains 100% synthetic base oils with synthetic fibers and fillers that provide a sure seal. The base fluids provide a very low coefficient of expansion (from -80°F to 500°F) while being oil resistant. The solid synthetic fibers and fillers provide a sure seal and are inert to most services.

SERVICE RECOMMENDATIONS

Desco 625 Pak can be used in hydrocarbons, steam, water, sour gas and sour crude. It is pumpable with a high pressure (10,000 psi) lubrication hand gun.

TYPICAL CHARACTERISTICS

Appearance	Green, grainy
NLGI	>6
Penetration (ASTM D217)	30-60
Base Oil	Synthetic
Base Oil Viscosity	60,000 cSt at 25°C
Base Oil Pour Point	-40°F (-40°C)
Solids Content	Synthetic fibers / fillers
Specific Gravity	1.4
Density (lb/gal)	11.9
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>450°F (260°C)
Temperature Range	-80°F to 500°F (-62°C to 260°C)

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LP625510	"B" stick 3/8" x 1 1/2"	100 /can
LP625550	"B" stick 3/8" x 1 1/2"	500 /can
LP625150	"J" stick 1 3/8" x 8 1/2"	16 /box
LP625425	10 lb Pail, 1" x 1/4" Coil	Pail

DO NOT USE IN OXYGEN SERVICE.

