

LUBRICANTS**Desco 750***High Temperature Hydrocarbon Service*DESCRIPTION

Desco 750 is formulated with 100% synthetic oils and contains solid lubricants for effective lubrication at temperatures to 900°F.

SERVICE RECOMMENDATIONS

Desco 750 can be used in aliphatic hydrocarbons, asphalt, hot oil, lubricating oils and steam.

TYPICAL CHARACTERISTICS

Appearance	Black, smooth, tacky
NLGI	3
Penetration (ASTM D217)	225-255
Worked Penetration, 60x (ASTM D217)	225-255
Base Oil	Synthetic and natural ester
Base Oil Viscosity	500 cSt at 40°C
Base Oil Pour Point	-4°F (-16 °C)
Thickener	Inorganic
Additives	Antioxidant package
Specific Gravity	1.0
Density (lb/gal)	8.6
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>550°F (288°C)
Temperature Range	-20°F to 900°F (-29°C to 482°C)
Storage Stability	Pass
Resistance to Water (FTM 5415)	Pass
Resistance to Mineral Spirits (FTM 5415 mod)	Pass
Resistance to HCl(aq)	Pass

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LL750110	"B" stick 3/8" x 1 1/2"	72 /box
LL750115	"C" stick 7/16" x 2 1/8"	32 /box
LL750130	"D" stick 1/2" x 2 1/4"	28 /box
LL750140	"G" stick 5/8" x 3 1/2"	14 /box
LL750150	"J" stick 1 3/8" x 8 1/2"	16 /box
LL750160	"K" stick 1 1/2" x 10 1/2"	12 /box
LL750200	14 oz. x 10	Cartridge
LL750010	10 lb	Can
LL750020	20 lb	Can
LL750040	40 lb	Pail
LL750120	120 lb	Keg
LL750400	400 lb drum c/w liner	Drum

DO NOT USE IN OXYGEN SERVICE.

