

LUBRICANTS

Desco 960

Body Fill



DESCRIPTION

Desco 960 is formulated for valves that contain body cavities. It is an economical body fill that will displace water and other containments. Chemola™ Desco 960 has high metal adhesion to lubricate and seal gates as they enter the body cavity.

SERVICE RECOMMENDATIONS

Desco 960 is excellent for lubricating valves, post-hydrotesting, prior to storage or shipping.

TYPICAL CHARACTERISTICS

Appearance	Black, smooth
NLGI	2
Penetration (ASTM D217)	265-295
Worked Penetration, 60x (ASTM D217)	265-295
Base Oil	Mineral oil 145
Base Oil Viscosity	cSt at 40°C
Base Oil Pour Point	-10°F (-23°C)
Thickener	Inorganic
Additives	Antioxidant/corrosion inhibitor package
Solids Content	Graphite
Specific Gravity	0.9
Density (lb/gal)	7.8
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>400°F (204°C)
Temperature Range	-18°F to 350°F (-28°C to 177°C)

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LL960200	14 oz. x 10	Cartridge
LL960010	10 lb	Can
LL960020	20 lb	Can
LL960040	35 lb	Pail
LL960120	120 lb	Keg
LL960400	400 lb drum c/w liner	Drum

DO NOT USE IN OXYGEN SERVICE.

