

LUBRICANTS**Desco 960**
Body FillDESCRIPTION

Desco 960 is formulated for valves that contain body cavities. It is an economical body fill that will displace water and other containments. Chemola™ Desco 960 has high metal adhesion to lubricate and seal gates as they enter the body cavity.

SERVICE RECOMMENDATIONS

Desco 960 is excellent for use in lubricating valves after hydrostatic testing for storage or shipping.

TYPICAL CHARACTERISTICS

Appearance	Gray, smooth
NLGI	2
Penetration (ASTM D217)	255-265
Worked Penetration, 60x (ASTM D217)	255-265
Base Oil	Mineral oil
Base Oil Viscosity	145 cSt at 40°C
Base Oil Pour Point	-10°F (-23 °C)
Thickener	Inorganic
Additives	Antioxidant/corrosion inhibitor package
Specific Gravity	1.5
Density (lb/gal)	12.6
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>450°F (232°C)
Temperature Range	0°F to 300°F (-18°C to 149°C)

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LL960200	14 oz. x 10	Cartridge
LL960010	10 lb	Can
LL960020	20 lb	Can
LL960040	35 lb	Pail
LL960120	120 lb	Keg
LL960400	400 lb drum c/w liner	Drum

DO NOT USE IN OXYGEN SERVICE.