

**INJECTABLE PACKING****Desco Black Stem-Pak**  
*High Temp Injectable Packing*DESCRIPTION

Desco Black Stem-Pak is a non-curing, pumpable packing that contains a blend of fibers and fillers in synthetic fluids. Black Stem Pak is specifically designed for high temperature hydrocarbon service.

SERVICE RECOMMENDATIONS

Desco Black Stem-Pak can be used in aliphatic hydrocarbons, asphalt, hot oil and steam and is excellent in geothermal applications. It is pumpable with a high pressure (10,000 psi) lubrication hand gun.

TYPICAL CHARACTERISTICS

Appearance	Black
NLGI	>6
Penetration (ASTM D217)	50-60
Base Oil	Synthetic and natural esters
Base Oil Viscosity	500 cSt at 40°C
Base Oil Pour Point	-4°F (-16°C)
Solids Content	Synthetic fibers / fillers
Specific Gravity	1.4
Density (lb/gal)	11.8
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>550°F (288°C)
Temperature Range	-90°F to 750°F (-40°C to 399°C)

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LP823110	"B" stick 3/8" x 1 1/2"	72 /box
LP823115	"C" stick 7/16" x 2 1/8"	32 /box
LP823130	"D" stick 1/2" x 2 1/4"	28 /box
LP823140	"G" stick 5/8" x 3 1/2"	14 /box
LP823150	"J" stick 1 3/8" x 8 1/2"	16 /box
LP823160	"K" stick 1 1/2" x 10 1/2"	12 /box
LP823812	1" x 1/8" ribbon x 12	Pail
LP823010	10 lb	Can

**DO NOT USE IN OXYGEN SERVICE.**