

SPECIALTY**Desco Dry Moly***Extreme Temperature Lubricant*DESCRIPTION

Desco Dry Moly Lube is an extreme temperature pressure lubricant. It is inert to water, oil, alkalies and most acids.

Desco Dry Moly Lube leaves a dry lubricated surface. It is especially suitable in areas where oil and grease cannot be used. Typical uses are automotive, refineries, chemical plants, paper mills, foundries, machine shops and other manufacturing facilities. Desco Dry Moly Lube is a heavy concentrate of micro-sized colloidal molybdenum disulfide lubricating solids in a fast evaporating carrier that has exceptional penetrating and spreading ability. It is a tough, nonconductive, dry film lubricant with strong surface bond after the carrier evaporates. It does not attract or retain grit. It is resistant to extreme temperatures and to chemical degradation. It dries to the touch in 60 seconds.

- Shake can vigorously before use
- Clean and dry surface to be coated
- Hold can 8 to 10 inches from surface
- Apply thin uniform coating
- Invert can and clear nozzle with a jet of clear gas after each use
- Desco Dry Moly can be removed with chlorinated solvent

TYPICAL CHARACTERISTICS

Appearance	Black
------------	-------

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LM932500	12 oz. aerosol	12/ ctn.

