

INJECTABLE PACKING**Desco Extreme-Pak***Extreme Temperature Injectable Packing*DESCRIPTION

Desco Extreme-Pak is a pumpable packing and sealant specially formulated for water and steam service under high- and low-temperature conditions. It is pumpable using high-pressure (10,000 PSI) lubrication hand gun even at sub-zero temperatures. Chemola™ Desco Extreme-Pak contains silicone oils with inert fillers and synthetic fibers.

SERVICE RECOMMENDATIONS

Aqueous solutions, hydrocarbons (low temperature), steam and water.

TYPICAL CHARACTERISTICS

| | |
|----------------------------|---------------------------------|
| Appearance | Blue |
| NLGI | >6 |
| Penetration (ASTM D217) | 50-65 |
| Base Oil | Silicone oil |
| Base Oil Viscosity | 40,000 cSt at 25°C |
| Base Oil Pour Point | -65°F (-54°C) |
| Solids Content | Synthetic fibers / fillers |
| Specific Gravity | 1.5 |
| Density (lb/gal) | 12.3 |
| Dropping Point (ASTM D566) | >500°F (260°C) |
| Flash Point | >620°F (326°C) |
| Temperature Range | -70°F to 600°F (-56°C to 315°C) |

PACKAGING INFORMATION

| PART # | UNIT SIZE | CONTAINER |
|----------|----------------------------|-----------|
| LP859110 | "B" stick 3/8" x 1 1/2" | 72 /box |
| LP859150 | "J" stick 1 3/8" x 8 1/2" | 16 /box |
| LP859160 | "K" stick 1 1/2" x 10 1/2" | 12 /box |
| LP859040 | 40 lb | Pail |

DO NOT USE IN OXYGEN SERVICE.

