

INJECTABLE PACKING**Desco Green Wellhead Pak**
Packing EnergizerDESCRIPTION

Desco Green Wellhead Packing is a proprietary packing formulation that has been developed primarily for the energizing of elastomer seals in crossover bushings in wellhead applications. It has also been used quite successfully as a packing energizer in blowout preventers. A blend of silicone oils and inert synthetic fibers allows for lubrication and the necessary bridging capabilities.

TYPICAL CHARACTERISTICS

Appearance	Green
NLGI	>6
Penetration (ASTM D217)	10-30
Base Oil	Silicone oil
Base Oil Viscosity	60,000 cSt at 25°C
Base Oil Pour Point	-40°F (-40°C)
Solids Content	Synthetic fibers / fillers
Specific Gravity	1.3
Density (lb/gal)	10.5
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>500°F (260°C)
Temperature Range	-70°F to 250°F (-57°C to 121°C)

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LP836150	"J" stick 1 3/8" x 8 1/2"	16 /box
LP836170	3/4" X 4" stick	10 /box
LP836581	5/8" x 1" stick	35 /box

DO NOT USE IN OXYGEN SERVICE.

