

**INJECTABLE PACKING****Desco TFE Versi-Pak**  
*Injectable Packing Sealant*DESCRIPTION

Desco TFE Versi-Pak is an injectable packing compound containing TFE-fluorocarbon particles blended into a synthetic binder. It is a highly versatile and durable self molding packing for use in stuffing boxes and for all types of valves, pumps and mechanical equipment. It can be either pre-formed manually or pumped into place with a high pressure (10,000 PSI) grease gun. TFE Versi-Pak is chemically stable and resistant to most chemicals over a wide pH range.

SERVICE RECOMMENDATIONS

Desco TFE Versi-Pak is a permanent packing which can be supplemented and does not need to be replaced.

TYPICAL CHARACTERISTICS

Appearance	White, grainy, sticky
NLGI	6
Penetration (ASTM D217)	80-90
Base Oil	Synthetic
Base Oil Viscosity	650 cSt at 100°C
Base Oil Pour Point	41°F (5°C)
Solids Content	PTFE
Specific Gravity	1.6
Density (lb/gal)	13.7
Dropping Point (ASTM D566)	392°F (200°C)
Flash Point	-20°F to 450°F (-29°C to 232°C)
Temperature Range	0°F to 400°F (-18°C to 204°C)

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LP815110	"B" stick 3/8" x 1 1/2"	72 /box
LP815115	"C" stick 7/16" x 2 1/8"	32 /box
LP815130	"D" stick 1/2" x 2 1/4"	28 /box
LP815140	"G" stick 5/8" x 3 1/2"	14 /box
LP815150	"J" stick 1 3/8" x 8 1/2"	16 /box
LP815160	"K" stick 1 1/2" x 10 1/2"	12 /box
LP815010	10 lb	Can
LP815020	25 lb	Can
LP815040	40 lb	Pail
LP815120	120 lb	Keg

**DO NOT USE IN OXYGEN SERVICE.**