

SPECIALTY**Desco Valve Cut***Frees Corroded and Frozen Valves*DESCRIPTION

Desco Valve Cut is a formulated multi-ingredient, semi-fluid combination of penetrants and lubricants designed to dissolve and cut residual gums, laquer deposits, inert solids and corrosion deposits that make valves non-functioning and hard to operate. Although not all valves are recoverable with Valve Cut, with periodic use many operators have found that valves remain operable through years of usage under severe conditions.

SERVICE RECOMMENDATIONS

For neglected valves. Helps to free frozen and non-sealing valves so that routine maintenance can be commenced. When the valve is again operational Chemola™ Desco Valve Cut must be purged from the valve by injecting the recommended Chemola™ Desco Synthetic Lubricant/Sealant for the particular service of the valve.

TYPICAL CHARACTERISTICS

Appearance	Black, smooth
NLGI	1
ASTM penetration	300 - 330
Appearance	inorganic
Thickener	Black, smooth
Specific Gravity	1.1
Density (lb/gal)	8.8
Flash Point	196°F (91°C)
Temperature range	-40°F to +400°F (-40°C to +204°C)

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LM531200	14 oz. x 10	Cartridge
LM531010	10 lb can	12 /case
LM531001	1 pt	12 /case
LM531020	25 lb	Can
LM531040	45 lb	Pail
LM531120	120 lb	Keg
LM531400	400 lb	Drum

DO NOT USE IN OXYGEN SERVICE.