

SNIPER™ LUBRICATION EQUIPMENT**AX Series***Drum Pump, Air, 120 lb & 400 lb*DESCRIPTION

GRM offers a variety of air driven drum pumps to suit your application. The pumps are rugged and precision manufactured to operate with all types of light or heavy material and in hot or cold weather to NLGI-4. All pumps include standard components necessary to start your job immediately.

Optional accessories are available to enhance your SNIPER™ drum pump efficiency.

SPECIFICATIONS

DESCRIPTION	PART #	
	GG716000	GG755000
Capacity	120 lb	400 lb
	16 gallon	55 gallon
Air Motor Ratio	100:1	70:1
Air Motor	Alemite	Alemite
MAX. Air Inlet	150 PSI	150 PSI
*Output	15 oz /minute	12 lb /minute
Recommended Air Inlet	100-105 PSI	100-105 PSI
Discharge Pressure	10,000 PSI	7,000 PSI
**Hose Assembly	10 ft	10 ft
Weight	60 lbs	65 lbs



120 lb - GG716000

* Based on MAX. discharge pressure with NLGI-2 lubricant at 25°C

** Hose assembly consists of straight and Z swivel, check valve with pressure release, needle/ball valve, giant button-head coupler, gauge and tee

OPTIONS

- Hoses
- Hoses/coupler
- Z-swivel
- Tees
- Gauge
- Combinations of the above



400 lb - GG755000