

**SNIPER™ LUBRICATION EQUIPMENT****AX Series***Bucket Pump, Air*DESCRIPTION

SNIPER™ Air Operated Bucket Pumps are needed for high-pressure applications. Benefits include operating ease and smooth efficiency. These pumps are rugged, long lasting, and precision manufactured. These pump's strong spring and follower plate assembly assures positive priming of all types of light or heavy materials in hot or cold weather to NLGI-4.

SPECIFICATIONS

DESCRIPTION	PART #	
	GG455000	GG655000
Air Inlet	1/4" NPSI	1/4" NPSI
Material Outlet	3/8" NPT	3/8" NPT
Air Motor	Alemite	Alemite
Discharge Pressure	15,000 PSI	15,000 PSI
Optimum Operating Pressure	10,500 PSI	10,500 PSI
Piston Diameter x Stroke	2.438" x 1.625"	2.438" x 1.625"
Measurements (Unit Only)	40" x 18"	40" x 24"
Approx. Net Weight	75 lbs	82 lbs



GG455000

GG655000

OPTIONS

- Hoses
- Z-swivel
- Gauge
- Hose/Coupler
- Tees
- Combinations of the above

ORDERING INFO

DESCRIPTION	PART #
10 lb Bucket Pump, Air	GG455000
35-50 lb Bucket Pump, Air	GG655000
Repair Kit	GG716010