TECHNICAL

LUBRICANTS

Steam-Xtreme Plus

Premium Steam-Resistant Lubricant/Sealant

GRM FLOW PRODUCTS

DESCRIPTION

Steam-Xtreme Plus is a premium, water insoluble synthetic valve lubricant formulated for extreme high temperature environments such as SAGD, steam injection and geothermal applications. Extensive laboratory and field testing confirms that Desco Steam-Xtreme Plus withstands the temperatures and conditions of steam-assisted gravity drainage, allowing valves to maintain a positive seal during operations. Withstands the maximum pressure rating of the valve.

SERVICE RECOMMENDATIONS

SAGD, steam injection, and geothermal wells.

TYPICAL CHARACTERISTICS

Appearance	Black, tacky
NLGI	2.5
Penetration (ASTM D217)	250-270
Penetration 60x (ASTM D217)	250-270
Base Oil	Synthetic blend
Base Oil Viscosity	600 cSt at 100°C
Base Oil Viscosity Index	173
Thickener	Inorganic
Additives	Corrosion inhibitors
Solids Content	Molybdeum disulfide
Specific Gravity	1.0
Resistance to water spray (ASTM D4049)	0.3%
Dropping Point (ASTM D566)	>580°F (308°C)
Flash Point	392°F (200°C)
Temperature Range	40°F to 750°F (5°C to 400°C)

PACKAGING INFORMATION

PART #	UNIT SIZE	CONTAINER
LLSXT040	40 lb	Pail
LLSXT120	120 lb	Keg
LLSXT400	400 lb drum c/w liner	Drum

DO NOT USE IN OXYGEN SERVICE.

#310, 8810 - 15th Street
Edmonton, Alberta, Canada T6P 0B9
(780) 416-4823
sales@grmflow.com