

PRESSURE GAUGES

4" | 100mm | Stainless Steel



FEATURES

- Design is ASME B40.1
- 1/2" NPT Bottom Mount
- Glycerine or Silicone Filled



SPECIFICATIONS

Accuracy:	±1% of full scale Grade 1A
Operating pressure:	75% of FS
Over pressure limit:	125% of FS
Case:	304 SS
Ring:	304 SS
Bourdon Tube:	NACE MR0175 316L SS
Socket:	NACE MR0175 316L SS
Movement:	304 SS
Protection:	IP-65
Dial face plate:	Aluminium
Pointer:	Aluminium
Window:	Toughened Glass
Fill:	Glycerine
	Silicone Oil
Gasket/vent plug:	Nitrile Rubber (BUNA N)
Scale:	Dual Scale psi/kPa
Connection:	1/2" NPT

ORDERING INFO

PART #	PRESSURE RANGE
P1316003	0 - 15 psi/kPa
P1316004	0 - 30 psi/kPa
P1316005	0 - 60 psi/kPa
P1316007	0 - 100 psi/kPa
P1316011	0 - 160 psi/kPa
P1316012	0 - 200 psi/kPa
P1316013	0 - 300 psi/kPa
P1316016	0 - 600 psi/kPa
P1316020	0 - 1,000 psi/kPa
P1316024	0 - 1,500 psi/kPa
P1316025	0 - 2,000 psi/kPa
P1316027	0 - 3,000 psi/kPa
P1316028	0 - 3,500 psi/kPa
P1316030	0 - 5,000 psi/kPa
P1316035	0 - 10,000 psi/kPa