

PRESSURE GAUGES

2.5" & 4" | Stainless Steel



FEATURES

- Design is ASME B40.1
- 1/2" NPT Bottom Mount, 4" Face
- 1/4" NPT Bottom Mount, 2.5" Face
- Glycerine or Silicone Filled (Optional)
- NACE MR0175



SPECIFICATIONS, 4" FACE

Accuracy:	±1% of full scale Grade 1A
Operating pressure:	75% of FS
Over pressure limit:	125% of FS
Case:	304 SS
Ring:	304 SS
Bourdon Tube:	NACE MR0175 316L SS
Socket:	NACE MR0175 316L SS
Movement:	304 SS
Protection:	IP-65
Dial face plate:	Aluminium
Pointer:	Aluminium
Window:	Toughened Glass
Fill:	Glycerine
Gasket/vent plug:	Nitrile Rubber (BUNA N)
Scale:	Dual Scale psi/kPa
Connection:	1/2" NPT

ORDERING INFO

1/4" NPT Bottom Mount, 2.5" Face

PART #	PRESSURE RANGE
P1113003	0-15 psi/kPa
P1113004	0-30 psi/kPa
P1113005	0-60 psi/kPa
P1113006	0-75 psi/kPa
P1113007	0-100 psi/kPa
P1113011	0-160 psi/kPa
P1113012	0-200 psi/kPa
P1113013	0-300 psi/kPa
P1113014	0-400 psi/kPa
P1113015	0-500 psi/kPa
P1113016	0-600 psi/kPa
P1113017	0-700 psi/kPa
P1113018	0-800 psi/kPa
P1113019	0-900 psi/kPa
P1113020	0-1000 psi/kPa
P1113024	0-1500 psi/kPa
P1113025	0-2000 psi/kPa
P1113026	0-2500 psi/kPa
P1113027	0-3000 psi/kPa
P1113028	0-3500 psi/kPa
P1113029	0-4000 psi/kPa
P1113030	0-5000 psi/kPa
P1113031	0-6000 psi/kPa
P1113035	0-10,000 psi/kPa
P1113038	0-15,000 psi/kPa

1/2" NPT Bottom Mount, 4" Face

PART #	PRESSURE RANGE
P1316003	0-15 psi/kPa
P1316004	0-30 psi/kPa
P1316005	0-60 psi/kPa
P1316007	0-100 psi/kPa
P1316011	0-160 psi/kPa
P1316012	0-200 psi/kPa
P1316013	0-300 psi/kPa
P1316014	0-400 psi/kPa
P1316015	0-500 psi/kPa
P1316016	0-600 psi/kPa
P1316020	0-1000 psi/kPa
P1316024	0-1500 psi/kPa
P1316025	0-2000 psi/kPa
P1316027	0-3000 psi/kPa
P1316028	0-3500 psi/kPa
P1316030	0-5000 psi/kPa
P1316035	0-10,000 psi/kPa

SPECIFICATIONS, 2.5" FACE

Accuracy:	±1.6% of full scale
Operating pressure:	75% of FS
Over pressure limit:	125% of FS
Case:	304 SS
Ring:	304 SS
Bourdon Tube:	NACE MR0175 316L SS
Socket:	NACE MR0175 316L SS
Movement:	304 SS
Protection:	IP-65
Dial face plate:	Aluminium
Pointer:	Aluminium
Window:	Toughened Glass
Fill:	Glycerine
Gasket/vent plug:	Nitrile Rubber (BUNA N)
Scale:	Dual Scale psi/kPa
Connection:	1/4" NPT

